



quadrix

The rugged hand-held with valuable features

Top features:

Frequency management

radiomatic® report


radiomatic® infrakey

HBC Safety Features

... and much more



Quality in Control.



Highlights:




radiomatic® iLOG

This clever electronic key enables the quick activation of a spare transmitter if the original transmitter is damaged. This means service without expensive downtime.



Frequency management (optional)

An automated frequency management via 2.4 GHz technology or DECT ensures interruption-free radio operation without frequency conflicts.



radiomatic® infrakey (optional)

With this option, an infrared connection between the transmitter and the receiver is necessary to switch on the system. This protects the operator from unintended crane / machine movements.



HBC Safety Features (optional)

In emergencies, radiomatic® shock-off / roll-detect / zero-g / inclination switch can trigger an automatic shutdown of the control and thus ensure additional safety.



radiomatic® report (optional)

This feature protects the control from unauthorized use. It enables the blocking of safety-relevant functions for non-authorized personnel as well as the storage of useful operational data.

Carrying methods:



Belt clip.



Option:
carrying bag.

Applications:

Diverse cranes, lift equipment and machinery.



Version with trolley preselection.



Version with LED feedback.

Further details:

- 8 two-step HBC push buttons / STOP impact switch.
- LED for indication of operating / battery status.
- 2 rechargeable NiMH exchange batteries, approx. 30 h of continuous operating time (standard version).
- Robust plastic housing, protection class IP 65.
- Weight: 360 g (0.8 lbs.) including battery.
- Integrated all-around rubber shock absorber.
- Manual frequency switch.
- Further options: radiomatic® AFS (Automatic Frequency Selection), radiomatic® shock-off / roll-detect / zero-g / inclination switch, tandem operation, customized labeling, feedback by LED, preselection of trolley / hoist via push button (indication of selection status via LEDs).